

SAFETY DATA SHEET

SPECIALTY ELECTRONIC MATERIALS NETHERLANDS B.V.

Safety Data Sheet according to Reg. (EU) No 2015/830

Product name: MOLYKOTE™ G-N Plus Paste Revision Date: 16.10.2018

Version: 1.0

Date of last issue: -Print Date: 21.02.2020

SPECIALTY ELECTRONIC MATERIALS NETHERLANDS B.V. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name: MOLYKOTE™ G-N Plus Paste

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricants and lubricant additives

1.3 Details of the supplier of the safety data sheet COMPANY IDENTIFICATION

SPECIALTY ELECTRONIC MATERIALS NETHERLANDS B.V. HERBERT H. DOWWEG 5 P.O. Box 48 4542 NM HOEK NETHERLANDS

Customer Information Number:

800-3876-6838

SDSQuestion-EU@dupont.com

1.4 EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: +(31)-858880596 **Local Emergency Contact:** +(31)-858880596

The phone number of the national poisoning information center (NVIC). Intended solely to

inform professional rescuers in case of acute poisoning: +31 30 - 2748888

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008:

Serious eye damage - Category 1 - H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

Revision Date: 16.10.2018 Version: 1.0

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

Hazard pictograms



Signal word: DANGER

Hazard statements

H318 Causes serious eye damage.

Precautionary statements

P280 Wear eye protection/ face protection.

P305 + P351 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

+ P338 + if present and easy to do. Continue rinsing. Immediately call a POISON

P310 CENTER/doctor.

Contains Calcium hydroxide

2.3 Other hazards

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Inorganic and organic compounds, in mineral oil

3.2 Mixtures

This product is a mixture.

CASRN / EC-No. / Index-No.	REACH Registration Number	Concentration	Component	Classification: REGULATION (EC) No 1272/2008
CASRN 1305-62-0 EC-No. 215-137-3 Index-No.	-	>= 21,0 - <= 31,0 %	Calcium hydroxide	Skin Irrit 2 - H315 Eye Dam 1 - H318 STOT SE - 3 - H335

Substances with a workplace exposure limit

Revision Date: 16.10.2018 Version: 1.0

CASRN 8042-47-5	01-2119487078-27	>= 33,0 - <= 49,0 %	White mineral oil (petroleum)	Not classified
EC-No. 232-455-8			,	
Index-No.				

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash off with plenty of water.

Eye contact: Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

- **4.2 Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.
- **4.3 Indication of any immediate medical attention and special treatment needed Notes to physician:** Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably from an ophthalmologist. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical

Unsuitable extinguishing media: None known.

Page 3 of 15

Revision Date: 16.10.2018 Version: 1.0

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products: Silicon oxides Formaldehyde Carbon oxides Metal oxides Oxides of phosphorus Sulphur oxides

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health.

5.3 Advice for firefighters

Fire Fighting Procedures: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- **6.1 Personal precautions, protective equipment and emergency procedures:** Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.
- **6.2 Environmental precautions:** Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- **6.3 Methods and materials for containment and cleaning up:** Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections:

See sections: 7, 8, 11, 12 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling: Do not swallow. Do not get in eyes. Avoid prolonged or repeated contact with skin. Keep container tightly closed. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice.

Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Page 4 of 15

Revision Date: 16.10.2018 Version: 1.0

7.2 Conditions for safe storage, including any incompatibilities: Keep in properly labelled containers. Keep tightly closed. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: None known.

7.3 Specific end use(s): See the technical data sheet on this product for further information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
White mineral oil (petroleum)	ACGIH	TWA Inhalable	5 mg/m3
		fraction	
	NL WG	TLV-8hr Mist	5 mg/m3

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

Derived No Effect Level

Calcium hydroxide

Workers

Acute systemic effects		Acute lo	cal effects		n systemic ects	Long-term local effects	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	4 mg/m3	n.a.	n.a.	n.a.	1 mg/m3

Consumers

Acute systemic effects		Acute loc	cal effects	Long-term systemic effects			Long-term local effects		
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	4 mg/m3	n.a.	n.a.	n.a.	n.a.	1 mg/m3

White mineral oil (petroleum)

Workers

VVOIRCIS							
Acute systemic effects		Acute lo	cal effects	Long-term systemic effects		Long-term local effects	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	220 mg/kg	160	n.a.	n.a.
				bw/day	mg/m3		

Consumers

Acute systemic effects		Acute local effects		Long-te	Long-term systemic effects			Long-term local effects	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation

Page 5 of 15

Revision Date: 16.10.2018 Version: 1.0

n.a.	n.a.	n.a.	n.a.	n.a.	93 mg/kg	35	40 mg/kg	n.a.	n.a.
					bw/day	mg/m3	bw/day		

Predicted No Effect Concentration

Calcium hydroxide

Compartment	PNEC
Fresh water	0,49 mg/l
Marine water	0,32 mg/l
Intermittent use/release	0,49 mg/l
Sewage treatment plant	3 mg/l
Soil	1080 mg/kg

8.2 Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles. Chemical goggles should be consistent with EN 166 or equivalent.

Skin protection

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Wear clean, body-covering clothing.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit

requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.

Environmental exposure controls

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

Physical state paste
Color grey
Odor none

Odor Threshold

pH

Not applicable

Melting point/range

Melting point

No data available

Not applicable

Flash point closed cup > 200 °C

Evaporation Rate (Butyl Acetate

= 1)

Not applicable

Flammability (solid, gas) Not classified as a flammability hazard

Lower explosion limitNo data availableUpper explosion limitNo data availableVapor PressureNot applicableRelative Vapor Density (air = 1)No data available

Relative Density (water = 1) 1,35

Water solubility

Partition coefficient: n
No data available

No data available

octanol/water

Auto-ignition temperatureNo data availableDecomposition temperatureNo data availableDynamic ViscosityNot applicableKinematic ViscosityNot applicableExplosive propertiesNot explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weightNo data availableParticle sizeNo data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: Not classified as a reactivity hazard.

10.2 Chemical stability: Stable under normal conditions.

10.3 Possibility of hazardous reactions: Can react with strong oxidizing agents. When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapours. Safe handling conditions may be maintained by keeping vapour concentrations within the occupational exposure limit for formaldehyde.

10.4 Conditions to avoid: None known.

10.5 Incompatible materials: Oxidizing agents

10.6 Hazardous decomposition products: Formaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

11.1 Information on toxicological effects Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

As product: Single dose oral LD50 has not been determined.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Acute inhalation toxicity

Prolonged excessive exposure to mist may cause adverse effects.

As product: The LC50 has not been determined.

Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.

Serious eye damage/eye irritation

Revision Date: 16.10.2018 Version: 1.0

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Sensitization

For skin sensitization:

Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

Contains component(s) which did not cause cancer in laboratory animals.

Teratogenicity

Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.

Reproductive toxicity

Contains component(s) which did not interfere with reproduction in animal studies.

Mutagenicity

Contains a component(s) which were negative in in vitro genetic toxicity studies. Contains component(s) which were negative in animal genetic toxicity studies.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:

Calcium hydroxide

Acute oral toxicity

LD50, Rat, > 2 000 mg/kg OECD Test Guideline 425

Acute dermal toxicity

Based on data from similar materials LD50, Rabbit, > 2 500 mg/kg OECD Test Guideline 402

Acute inhalation toxicity

The LC50 has not been determined.

White mineral oil (petroleum)

Acute oral toxicity

LD50, Rat, > 5 000 mg/kg OECD Test Guideline 401

Acute dermal toxicity

LD50, Rabbit, > 2 000 mg/kg OECD Test Guideline 402 No deaths occurred at this concentration.

Page 9 of 15

Revision Date: 16.10.2018 Version: 1.0

Acute inhalation toxicity

LC50, Rat, male and female, 4 Hour, dust/mist, > 5 mg/l OECD Test Guideline 403

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

12.1 Toxicity

Calcium hydroxide

Acute toxicity to fish

Material is harmful to aquatic organisms (LC50/EC50/IC50 between 10 and 100 mg/L in the most sensitive species).

LC50, Gasterosteus aculeatus (threespine stickleback), 96 Hour, 457 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 49,1 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, 184,57 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, 3 Hour, 300,4 mg/l, OECD Test Guideline 209

Chronic toxicity to aquatic invertebrates

NOEC, 14 d, 32 mg/l

White mineral oil (petroleum)

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LL50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, > 100 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

LL50, Daphnia magna (Water flea), static test, 48 Hour, > 100 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, 100 mg/l, OECD Test Guideline 201

Chronic toxicity to fish

NOEC, Oncorhynchus mykiss (rainbow trout), 28 d, 1 000 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, 1 000 mg/l

12.2 Persistence and degradability

Calcium hydroxide

Biodegradability: No relevant data found.

White mineral oil (petroleum)

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions. Material is inherently biodegradable (reaches > 20% biodegradation in OECD test(s) for inherent biodegradability).

10-day Window: Fail **Biodegradation:** 0 - 24 % **Exposure time:** 28 d

Method: OECD Test Guideline 301B or Equivalent

12.3 Bioaccumulative potential

Calcium hydroxide

Bioaccumulation: Not applicable

White mineral oil (petroleum)

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and

7).

Partition coefficient: n-octanol/water(log Pow): 5,18 Measured

Bioconcentration factor (BCF): 1 900 Fish

12.4 Mobility in soil

Calcium hydroxide

No relevant data found.

White mineral oil (petroleum)

Potential for mobility in soil is low (Koc between 500 and 2000).

Partition coefficient (Koc): 510 Estimated.

12.5 Results of PBT and vPvB assessment

Calcium hydroxide

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

White mineral oil (petroleum)

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

12.6 Other adverse effects

Calcium hydroxide

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

White mineral oil (petroleum)

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Page 11 of 15

Revision Date: 16.10.2018 Version: 1.0

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not dump into any sewers, on the ground, or into any body of water. This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

SECTION 14: TRANSPORT INFORMATION

Classification for ROAD and Rail transport (ADR/RID):

14.1 UN number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable14.4 Packing group Not applicable

14.5 Environmental hazards Not considered environmentally hazardous based on

available data.

14.6 Special precautions for user No data available.

Classification for SEA transport (IMO-IMDG):

14.1 UN number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable14.4 Packing group Not applicable

14.5 Environmental hazards Not considered as marine pollutant based on available data.

14.6 Special precautions for user No data available.

14.7 Transport in bulk according to Annex I or II of MARPOL

73/78 and the IBC or IGC

Consult IMO regulations before transporting ocean bulk

Code

Classification for AIR transport (IATA/ICAO):

14.1 UN number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable

Page 12 of 15

14.4 Packing group Not applicable
14.5 Environmental hazards Not applicable
14.6 Special precautions for user No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACh Regulation (EC) No 1907/2006

This product contains only components that have been either pre-registered, registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH).,The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure thathis/her understanding of the regulatory status of this product is correct.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: Not applicable

ABM (Algemene Beoordelingsmethodiek): Please contact our product stewardship specialist via the Customer Information contact details in Section 1 for information on the assessment of substances and preparations within the context of the implementation of the water discharge policy.

15.2 Chemical safety assessment

Not applicable

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H315 Causes skin irritation. H318 Causes serious eye d

H318 Causes serious eye damage. H335 May cause respiratory irritation.

Page 13 of 15

Revision Date: 16.10.2018 Version: 1.0

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

Eve Dam. - 1 - H318 - Based on product data or assessment

Revision

Identification Number: 1676377 / A636 / Issue Date: 16.10.2018 / Version: 1.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

9	
ACGIH	USA. ACGIH Threshold Limit Values (TLV)
NL WG	Netherlands. Law on Labour conditions - Occupational Exposure Limits
TLV-8hr	Time Weighted Average
TWA	8-hour, time-weighted average
Eye Dam.	Serious eye damage
Skin Irrit.	Skin irritation
STOT SE	Specific target organ toxicity - single exposure

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada): ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG -International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet: SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory: TRGS - Technical Rule for Hazardous Substances: TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

SPECIALTY ELECTRONIC MATERIALS NETHERLANDS B.V. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

NL

Page 15 of 15