FABORY



Spiralstifte Typ gerade DIN 7343 ISO 8750 Federstahl 420-545 HV30 2,5X24MM

Artikelnummer	39140.025.024
Marke	-
UBB	950359055122
UNSPSC	31163201
EAN	8715492808165
PKG. von 200	Nur komplette Verpackung

Technische Parameter

Standards

Durchmesser	2.5 mm	DIN	7343
Länge	24 mm	ISO	8750
Material	Federstahl		
Material technisch	420-545 HV30		
Info	Warning: electroplating of these products may cause hydrogen embrittlement.Dimens d1 and d2 in above table are before mounting.V = minimum shear strength, double, in kN.The recommended tolerance class for the accommodating hole diameter d (nominal) is H12.Special features of coiled spring- type straight pins (spiral pins):These pins are used for connections or the positioning of two or more parts and may also be used as	sions	

shafts and hinge-,

stop- or carrierpins, and are easily disassembled.Thanks to their spiral shaped cross section (approximately 2.1/4 coils) these pins are very flexible and suitable for repeated use with dynamic loads. Equal stress distribution throughout their cross section against the hole wall produces a good press fit, which can absorb shear forces unaffected by the direction. The pins are chamfered at both ends, so they can easily be inserted and installed automatically.

Technische Spezifikation

a≈	0.7
d1 (max.)	2.78
d1 (min.)	2.65
d2 (max.)	2.4
D (mm)	2.5
L (mm)	24
V	3.9

Technische Zeichnung

