FABORY



ISO 8748 Federstahl 420-545 HV30 4X18MM

Artikelnummer	39150.040.018
Marke	-
UBB	950359070543
UNSPSC	31163201
EAN	8715492809827
PKG. von 200	Nur komplette Verpackung

Technische Parameter

Standards

Durchmesser 4 mm DIN 7344 Länge 18 mm ISO 8748 Material Federstahl Material technisch 420-545 HV30 Info Warning: electroplating of these products may cause hydrogen embrittlement.Dimensions d1 and d2 in above table are before mounting.V = minimum shear strength, double, in kN.The recommended tolerance class for the accommodating hole diameter d (nominal) is H12.Special features of coiled spring- type straight pins (spiral pins):These pins are used for				
Material Federstahl Material technisch 420-545 HV30 Info Warning: electroplating of these products may cause hydrogen embrittlement.Dimensions d1 and d2 in above table are before mounting.V = minimum shear strength, double, in kN.The recommended tolerance class for the accommodating hole diameter d (nominal) is H12.Special features of coiled spring- type straight pins (spiral pins):These pins are used for	Durchmesser	4 mm	DIN	7344
Info Warning: electroplating of these products may cause hydrogen embrittlement.Dimensions d1 and d2 in above table are before mounting.V = minimum shear strength, double, in kN.The recommended tolerance class for the accommodating hole diameter d (nominal) is H12.Special features of coiled spring- type straight pins (spiral pins):These pins are used for	Länge	18 mm	ISO	8748
Info Warning: electroplating of these products may cause hydrogen embrittlement.Dimensions d1 and d2 in above table are before mounting.V = minimum shear strength, double, in kN.The recommended tolerance class for the accommodating hole diameter d (nominal) is H12.Special features of coiled spring- type straight pins (spiral pins):These pins are used for	Material	Federstahl		
electroplating of these products may cause hydrogen embrittlement.Dimensions d1 and d2 in above table are before mounting.V = minimum shear strength, double, in kN.The recommended tolerance class for the accommodating hole diameter d (nominal) is H12.Special features of coiled spring- type straight pins (spiral pins):These pins are used for	Material technisch	420-545 HV30		
connections or the positioning of two or more parts and may also be used as shafts and hinge-, stop- or carrierpins, and are easily		Warning: electroplating of these products may cause hydrogen embrittlement.Dimens d1 and d2 in above table are before mounting.V = minimum shear strength, double, in kN.The recommended tolerance class for the accommodating hole diameter d (nominal) is H12.Special features of coiled spring- type straight pins (spiral pins):These pins are used for connections or the positioning of two or more parts and may also be used as shafts and hinge-, stop- or carrierpins,	sions	

disassembled.Thanks to their spiral shaped cross section (approximately 2.1/4 coils) these pins are very flexible and suitable for repeated use with dynamic loads. Equal stress distribution throughout their cross section against the hole wall produces a good press fit, which can absorb shear forces unaffected by the direction. The pins are chamfered at both ends, so they can easily be inserted and installed automatically.

Technische Spezifikation

a≈	1.1
d1 (max.)	4.3
d1 (min.)	4.15
d2 (max.)	3.9
D (mm)	4
L (mm)	18
V	13.5

Technische Zeichnung

