

Class	8.8
Class	8.8
Class	8.8
Class	8.8
Class	8.8
Class	8.8
Class	8.8
Class	8.8
Class	8.8
Class	8.8
Class	8.8
Driving features	Hexagon
Extra info	ISO metric
Head shape	Hexagon head
Material	Steel
Thread direction	Right
Surface treatment	Hot dip galvanized
Thread	Metric thread
Wrench width (s) (mm)	34
Wrench width (s) (mm)	34
Wrench width (s) (mm)	34
Wrench width (s) (mm)	34
Wrench width (s) (mm)	34
Wrench width (s) (mm)	34
Wrench width (s) (mm)	34
Wrench width (s) (mm)	34
Wrench width (s) (mm)	34
Wrench width (s) (mm)	34
Wrench width (s) (mm)	34
Wrench width (s) (mm)	34
Wrench width (s) (mm)	34
Wrench width (s) (mm)	34
Info	ISO metric hot dip galvanized bolts and screws are

FABORY

manufactured with
thread tolerance
class 6az (undersize)
before coating. After
galvanizing they will
fit into standard nuts
and threaded holes
with thread tolerance
class 6H.

Technical Specification

b (min.): 125mm<L≤200mm	56
b (min.): L>200mm	69
b (min.): L≤125mm	50
k	14
P	2.50
s	34