



Structural assembly set ISO metric thread EN 15048 Steel Hot dip galvanized 8.8/8 M16X180

Article number	01405.160.180
Brand	-
UBB	500613360584
UNSPSC	31161620
EAN	8715494428132
PKG. of 25	Full Box Only

Technical Parameters

recificar rarame		Otanualus	
Diameter	M16	EN	15048
Length	180 mm	ISO	4014/4032
Class	8.8/8		
Driving features	Hexagon		
Head shape	Hexagon head		
Material	Steel		
Thread direction	Right		
Surface treatment	Hot dip galvanized		
Thread	Metric thread		
Info	Full boxes only.European constructions must comply with the Construction Products Regulation (CPR) in order to ensure the safety of persons and objects.Generally, construction products according to harmonized European standards (hEN standards) should be used for this purpose. Bolting assemblies for non- preloaded structural		

Standards



bolting according CPR.Compared to 'common' bolts ISO 4014/4017 (previously DIN 931/933) and nuts ISO 4032 (DIN 934), bolts and nuts according to EN 15048 are additionally marked with 'SB' (Structural Bolting), and the packaging is provided with the CE-mark.The manufacturer of the assemblies is CE certified for their production.Bolts and nuts are packaged together in single sealed boxes.A Declaration of Performance (DoP) is available.ISO metric

Technical Specification

b (min.): 125mmL≤200mm	44
b (min.): L200mm	57
b (min.): L≤125mm	38
d-D	M16
k	10
L (mm)	180
m (max.)	14.8
Ρ	2
S	24

Technical Drawing

