
# **FABORY**



# Structural assembly set ISO metric thread EN 15048 Steel Hot dip galvanized 8.8/8 M20X110

| Article number | 01405.200.110 |
|----------------|---------------|
| Brand          | -             |
| UBB            | 500574461439  |
| UNSPSC         | 31161620      |
| EAN            | 8715494284028 |
| PKG. of 1      | Full Box Only |

## **Technical Parameters**

#### **Standards**

| Technical Parameters |  | Standards |           |
|----------------------|--|-----------|-----------|
| Diameter             | M20  | ISO       | 4014/4032 |
| Length               | 110 mm   | EN        | 15048     |
| Class                | 8.8/8  |           |           |
| Driving features     | Hexagon  |           |           |
| Head shape           | Hexagon head   |           |           |
| Material             | Steel  |           |           |
| Thread direction     | Right  |           |           |
| Surface treatment    | Hot dip galvanized   |           |           |
| Thread               | Metric thread  |           |           |
| Info                 | Full boxes only.European constructions must comply with the Construction Products Regulation (CPR) in order to ensure the safety of persons and objects.Generally, construction products according to harmonized European standards (hEN standards) should be used for this purpose. Bolting |           |           |

assemblies for nonpreloaded structural bolting according to EN 15048-1 are compliant with the

**CPR.Compared** to 'common' bolts ISO 4014/4017 (previously DIN 931/933) and nuts ISO 4032 (DIN 934), bolts and nuts according to EN 15048 are additionally marked with 'SB' (Structural Bolting), and the packaging is provided with the CE-mark.The manufacturer of the assemblies is CE certified for their production.Bolts and nuts are packaged together in single sealed boxes.A Declaration of Performance (DoP) is available.ISO metric

# **Technical Specification**

| b (min.):<br>125mmL≤200mm | 52   |
|---------------------------|------|
| b (min.): L200mm          | 65   |
| b (min.): L≤125mm         | 46   |
| d-D                       | M20  |
| k                         | 12.5 |
| L (mm)                    | 110  |
| m (max.)                  | 18   |
| Р                         | 2.5  |
| S                         | 30   |

## **Technical Drawing**

