



Bosch Demolition hammer GSH 27 VC

Article No.	B4375.000.025
Brand	-
UBB	500620053636
UNSPSC	27112705
EAN	3165140524322
PKG. of 1	Full Box Only

Technical Parameters

Drive size	28-mm- binnenzeskant
------------	-------------------------

Drive size	28-mm- binnenzeskant
------------	-------------------------

Drive size	28-mm- binnenzeskant
------------	-------------------------

Drive size	28-mm- binnenzeskant
------------	-------------------------

Drive size	28-mm- binnenzeskant
------------	-------------------------

Drive size	28-mm- binnenzeskant
------------	-------------------------

Drive size	28-mm- binnenzeskant
------------	-------------------------

Drive size	28-mm- binnenzeskant
------------	-------------------------

Drive size	28-mm- binnenzeskant
------------	-------------------------

Drive size	28-mm- binnenzeskant
------------	-------------------------

Drive size	28-mm- binnenzeskant
------------	-------------------------

Drive size	28-mm- binnenzeskant
------------	-------------------------

Height (mm)	750
-------------	-----

Standards

Height (mm)	750
Height (mm)	750
Height (mm)	750
Height (mm)	750
Height (mm)	750
Height (mm)	750
Height (mm)	750
Height (mm)	750
Height (mm)	750
Height (mm)	750
Height (mm)	750
Impact energy	62 J
Impact energy	62 J
Impact energy	62 J
Impact energy	62 J
Impact energy	62 J
Impact energy	62 J
Impact energy	62 J
Impact energy	62 J
Impact energy	62 J
Impact energy	62 J
Impact energy	62 J
Impact energy	62 J
Impact energy	62 J
Impact energy	62 J
Impact energy	62 J
vibration level when drilling (m/s ²)	8,5
vibration level when drilling (m/s ²)	8,5
vibration level when drilling (m/s ²)	8,5
vibration level when drilling (m/s ²)	8,5
vibration level when drilling (m/s ²)	8,5
vibration level when drilling (m/s ²)	8,5
vibration level when drilling (m/s ²)	8,5
vibration level when drilling (m/s ²)	8,5
vibration level when drilling (m/s ²)	8,5
vibration level when drilling (m/s ²)	8,5
vibration level when drilling (m/s ²)	8,5


 THE FASTENING SOLUTIONS GROUP

OUR COURSE

vibration level when drilling (m/s²) 8,5



vibration level when drilling (m/s²) 8,5

vibration level when drilling (m/s²) 8,5

Vibration level when chiseling (m/s²) 8.5

Vibration level when chiseling (m/s²) 8.5

Vibration level when chiseling (m/s²) 8.5

Vibration level when chiseling (m/s²) 8.5

Vibration level when chiseling (m/s²) 8.5

Vibration level when chiseling (m/s²) 8.5

Vibration level when chiseling (m/s²) 8.5

Vibration level when chiseling (m/s²) 8.5

Vibration level when chiseling (m/s²) 8.5

Vibration level when chiseling (m/s²) 8.5

Vibration level when chiseling (m/s²) 8.5

Vibration level when chiseling (m/s²) 8.5

Wattage 2000 Watt

Wattage 2000 Watt

Wattage 2000 Watt

Wattage 2000 Watt

Wattage 2000 Watt

Wattage 2000 Watt

Wattage 2000 Watt

Wattage 2000 Watt

Wattage 2000 Watt

Wattage 2000 Watt

Wattage 2000 Watt

Wattage 2000 Watt

Width (mm) 810

Width (mm) 810

Width (mm) 810

UR COURSE
Width (mm) 810
SEE THE STANDARD
IN FASTENING SOLUTIONS

Width (mm) 810

Width (mm) 810

Width (mm) 810

Width (mm) 810

Width (mm) 810

Width (mm) 810

Width (mm) 810

Width (mm) 810