

**MOLYKOTE(R) G-4500 FM MULTI-PURPOSE
SYNTHETIC GREASE**

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.09.2015 |
| 1.4 | 21.10.2015 | 848033-00005 | Date of first issue: 28.11.2014 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOLYKOTE(R) G-4500 FM MULTI-PURPOSE SYNTHETIC GREASE

Product code : 000000000003160718, 000000000003160718

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Lubricants and lubricant additives

1.3 Details of the supplier of the safety data sheet

Company : Dow Corning Europe S.A.
rue Jules Bordet - Parc Industriel - Zone C
B-7180 Seneffe

Telephone : English Tel: +49 611237507
Deutsch Tel: +49 611237500
Français Tel: +32 64511149
Italiano Tel: +32 64511170
Español Tel: +32 64511163

E-mail address of person
responsible for the SDS : sdseu@dowcorning.com

1.4 Emergency telephone number

Dow Corning (Barry U.K. 24h) Tél: +44 1446732350
Dow Corning (Wiesbaden 24h) Tél: +49 61122158
Dow Corning (Seneffe 24h) Tel: +32 64 888240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)
Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)
Not a hazardous substance or mixture.

Additional Labelling:

EUH210 Safety data sheet available on request.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

**MOLYKOTE(R) G-4500 FM MULTI-PURPOSE
SYNTHETIC GREASE**

Version 1.4 Revision Date: 21.10.2015 SDS Number: 848033-00005 Date of last issue: 11.09.2015
Date of first issue: 28.11.2014

3.2 Mixtures

Chemical nature : Organic grease

Hazardous components

| Chemical name | CAS-No. EC-No. Registration number | Classification | Concentration (% w/w) |
|--------------------------------------|---|-------------------|--------------------------|
| Dec-1-ene, homopolymer, hydrogenated | 68037-01-4 500-183-1 01-2119486452-34 | Asp. Tox. 1; H304 | >= 50 - < 70 |
| White mineral oil (petroleum) | 8042-47-5 232-455-8 01-2119487078-27 | Asp. Tox. 1; H304 | >= 1 - < 10 |

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders : No special precautions are necessary for first aid responders.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing : None known.

MOLYKOTE(R) G-4500 FM MULTI-PURPOSE SYNTHETIC GREASE

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.09.2015 |
| 1.4 | 21.10.2015 | 848033-00005 | Date of first issue: 28.11.2014 |

media

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

MOLYKOTE(R) G-4500 FM MULTI-PURPOSE SYNTHETIC GREASE

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.4 | 21.10.2015 | 848033-00005 | 11.09.2015 |
| | | | Date of first issue: 28.11.2014 |

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | |
|-------------------------|--|
| Technical measures | : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : Use only with adequate ventilation. |
| Advice on safe handling | : Handle in accordance with good industrial hygiene and safety practice. Take care to prevent spills, waste and minimize release to the environment. |
| Hygiene measures | : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | |
|---|---|
| Requirements for storage areas and containers | : Keep in properly labelled containers. Store in accordance with the particular national regulations. |
| Advice on common storage | : Do not store with the following product types: Strong oxidizing agents |

7.3 Specific end use(s)

- | | |
|-----------------|---|
| Specific use(s) | : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. |
|-----------------|---|

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---------------------|---|-------------------------------|----------------------|---------|
| Calcium carbonate | 471-34-1 | TWA (inhalable dust) | 10 mg/m ³ | GB EH40 |
| Further information | For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts | | | |

**MOLYKOTE(R) G-4500 FM MULTI-PURPOSE
SYNTHETIC GREASE**

Version 1.4 Revision Date: 21.10.2015 SDS Number: 848033-00005 Date of last issue: 11.09.2015
Date of first issue: 28.11.2014

| | |
|---------------------|--|
| | contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used |
| | TWA (Respirable dust) 4 mg/m ³ GB EH40 |
| Further information | For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust. The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|-------------------|-----------|-----------------|----------------------------|----------------------|
| Calcium carbonate | Workers | Inhalation | Long-term systemic effects | 10 mg/m ³ |
| | Consumers | Inhalation | Long-term systemic effects | 10 mg/m ³ |
| | Consumers | Ingestion | Long-term systemic effects | 6.1 mg/kg bw/day |
| | Consumers | Ingestion | Acute systemic effects | 6.1 mg/kg bw/day |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

**MOLYKOTE(R) G-4500 FM MULTI-PURPOSE
SYNTHETIC GREASE**

Version 1.4 Revision Date: 21.10.2015 SDS Number: 848033-00005 Date of last issue: 11.09.2015
Date of first issue: 28.11.2014

| Substance name | Environmental Compartment | Value |
|--------------------------------------|---------------------------|-----------|
| Calcium carbonate | Sewage treatment plant | 100 mg/l |
| Aluminum hydroxide benzoate stearate | Fresh water | 0.1 mg/l |
| | Marine water | 0.01 mg/l |
| | Intermittent use/release | 1 mg/l |

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety glasses

Hand protection
Remarks : Wash hands before breaks and at the end of workday.

Skin and body protection : Skin should be washed after contact.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Grease

Colour : off-white

Odour : none

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : > 200 °C
Method: closed cup

Evaporation rate : Not applicable

**MOLYKOTE(R) G-4500 FM MULTI-PURPOSE
SYNTHETIC GREASE**

| | | | |
|----------------|------------------------------|-----------------------------|---|
| Version 1.4 | Revision Date: 21.10.2015 | SDS Number: 848033-00005 | Date of last issue: 11.09.2015 Date of first issue: 28.11.2014 |
|----------------|------------------------------|-----------------------------|---|

| | |
|--|--|
| Flammability (solid, gas) | : Not classified as a flammability hazard |
| Upper explosion limit | : No data available |
| Lower explosion limit | : No data available |
| Vapour pressure | : Not applicable |
| Relative vapour density | : No data available |
| Relative density | : 0.83 |
| Solubility(ies) | |
| Water solubility | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity | |
| Viscosity, dynamic | : Not applicable |
| Explosive properties | : Not explosive |
| Oxidizing properties | : The substance or mixture is not classified as oxidizing. |

9.2 Other information

| | |
|------------------|---------------------|
| Molecular weight | : No data available |
|------------------|---------------------|

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

| | |
|---------------------|---|
| Hazardous reactions | : Can react with strong oxidizing agents. |
|---------------------|---|

10.4 Conditions to avoid

| | |
|---------------------|---------------|
| Conditions to avoid | : None known. |
|---------------------|---------------|

10.5 Incompatible materials

| | |
|--------------------|--------------------|
| Materials to avoid | : Oxidizing agents |
|--------------------|--------------------|

MOLYKOTE(R) G-4500 FM MULTI-PURPOSE SYNTHETIC GREASE

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.09.2015 |
| 1.4 | 21.10.2015 | 848033-00005 | Date of first issue: 28.11.2014 |

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Dec-1-ene, homopolymer, hydrogenated:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Dec-1-ene, homopolymer, hydrogenated:

Species: Rabbit
Result: No skin irritation

White mineral oil (petroleum):

Species: Rabbit
Result: No skin irritation

**MOLYKOTE(R) G-4500 FM MULTI-PURPOSE
SYNTHETIC GREASE**

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.09.2015 |
| 1.4 | 21.10.2015 | 848033-00005 | Date of first issue: 28.11.2014 |

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Dec-1-ene, homopolymer, hydrogenated:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

White mineral oil (petroleum):

Species: Rabbit

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

Dec-1-ene, homopolymer, hydrogenated:

Test Type: Maximisation Test

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

White mineral oil (petroleum):

Test Type: Buehler Test

Exposure routes: Skin contact

Species: Guinea pig

Result: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Dec-1-ene, homopolymer, hydrogenated:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

**MOLYKOTE(R) G-4500 FM MULTI-PURPOSE
SYNTHETIC GREASE**

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.4 | 21.10.2015 | 848033-00005 | 11.09.2015 |
| | | | Date of first issue: 28.11.2014 |

Carcinogenicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Species: Rat
Application Route: Ingestion
Exposure time: 24 Months
Result: negative

Reproductive toxicity

Not classified based on available information.

Components:

Dec-1-ene, homopolymer, hydrogenated:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Skin contact
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Dec-1-ene, homopolymer, hydrogenated:

Species: Rat
NOAEL: 1,000 mg/kg
Application Route: Ingestion
Exposure time: 91 Days

White mineral oil (petroleum):

Species: Rat
LOAEL: > 160 mg/kg
Application Route: Ingestion
Exposure time: 90 Days

MOLYKOTE(R) G-4500 FM MULTI-PURPOSE SYNTHETIC GREASE

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.09.2015 |
| 1.4 | 21.10.2015 | 848033-00005 | Date of first issue: 28.11.2014 |

Species: Rat
LOAEL: ≥ 1 mg/l
Application Route: inhalation (dust/mist/fume)
Exposure time: 4 Weeks
Method: OECD Test Guideline 412

Aspiration toxicity

Not classified based on available information.

Components:

Dec-1-ene, homopolymer, hydrogenated:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

White mineral oil (petroleum):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Dec-1-ene, homopolymer, hydrogenated:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): $> 1,000$ mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): $> 1,000$ mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Scenedesmus capricornutum (fresh water algae)): $> 1,000$ mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Scenedesmus capricornutum (fresh water algae)): $1,000$ mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to bacteria : NOEC : 2 mg/l
Exposure time: 28 d
Method: OECD Test Guideline 301D

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 125 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

**MOLYKOTE(R) G-4500 FM MULTI-PURPOSE
SYNTHETIC GREASE**

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.09.2015 |
| 1.4 | 21.10.2015 | 848033-00005 | Date of first issue: 28.11.2014 |

Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211

White mineral oil (petroleum):

| | |
|--|--|
| Toxicity to fish | : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 |
| Toxicity to algae | : NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 |
| Toxicity to fish (Chronic toxicity) | : NOEC: 1,000 mg/l Exposure time: 28 d Species: Oncorhynchus mykiss (rainbow trout) |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOEC: 1,000 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) |

12.2 Persistence and degradability

Components:

Dec-1-ene, homopolymer, hydrogenated:

| | |
|------------------|--|
| Biodegradability | : Result: Not readily biodegradable. Biodegradation: 2 % Exposure time: 28 d Method: OECD Test Guideline 301D |
|------------------|--|

White mineral oil (petroleum):

| | |
|------------------|---|
| Biodegradability | : Result: Not readily biodegradable. Biodegradation: 31 % Exposure time: 28 d |
|------------------|---|

12.3 Bioaccumulative potential

Components:

Dec-1-ene, homopolymer, hydrogenated:

| | |
|--|------------------|
| Partition coefficient: n-octanol/water | : log Pow: > 6.5 |
|--|------------------|

12.4 Mobility in soil

No data available

**MOLYKOTE(R) G-4500 FM MULTI-PURPOSE
SYNTHETIC GREASE**

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 1.4 | 21.10.2015 | 848033-00005 | 11.09.2015 |
| | | | Date of first issue: 28.11.2014 |

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- | | |
|------------------------|---|
| Product | : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. |
| Contaminated packaging | : Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product. |

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

**MOLYKOTE(R) G-4500 FM MULTI-PURPOSE
SYNTHETIC GREASE**

| | | | |
|----------------|------------------------------|-----------------------------|---|
| Version 1.4 | Revision Date: 21.10.2015 | SDS Number: 848033-00005 | Date of last issue: 11.09.2015 Date of first issue: 28.11.2014 |
|----------------|------------------------------|-----------------------------|---|

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

The components of this product are reported in the following inventories:

| | |
|-----------|--|
| NZIoC | : All ingredients listed or exempt. |
| REACH | : All ingredients (pre-)registered or exempt. |
| TSCA | : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances. |
| AICS | : All ingredients listed or exempt. |
| IECSC | : All ingredients listed or exempt. |
| DSL | : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL). |
| ENCS/ISHL | : All components are listed on ENCS/ISHL or exempted from inventory listing. |
| KECI | : One or more ingredients are not listed or exempt. |
| PICCS | : Consult your local Dow Corning office. |
| TCSI | : All ingredients listed or exempt. |

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.

Full text of other abbreviations

| | |
|---------------|--|
| Asp. Tox. | : Aspiration hazard |
| GB EH40 | : UK. EH40 WEL - Workplace Exposure Limits |
| GB EH40 / TWA | : Long-term exposure limit (8-hour TWA reference period) |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous

MOLYKOTE(R) G-4500 FM MULTI-PURPOSE SYNTHETIC GREASE

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.09.2015 |
| 1.4 | 21.10.2015 | 848033-00005 | Date of first issue: 28.11.2014 |

Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006

DOW CORNING

**MOLYKOTE(R) G-4500 FM MULTI-PURPOSE
SYNTHETIC GREASE**

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.09.2015 |
| 1.4 | 21.10.2015 | 848033-00005 | Date of first issue: 28.11.2014 |
